

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	340/85 R 28 (13.6 R 28)
LI/SS	127 A8/B

## Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1289
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3890
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000593
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	965	1120	1280	1435	1595	1750
40	965	1120	1280	1435	1595	1750
30	1035	1200	1370	1540	1710	1875
10 LT	1290	1505	1715	1925	2135	2345
10 HT	1035	1200	1370	1540	1710	1875

Printed on 4/27/2024 12:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..