

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

## Dimensions US Standard

Usa code	94033126
Section Width (inch)	17.2
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	26
Rolling Circumference (inch)	174.1
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000654
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3030	3530	4020	4520	5020	5500
25	3030	3530	4020	4520	5020	5500
20	3250	3780	4310	4840	5370	5900
5 LT	4070	4730	5400	6060	6720	7390
5 HT	3250	3780	4310	4840	5370	5900

Printed on 4/27/2024 5:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..