

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	480/80 R 46 (18.4 R 46)
LI/SS	164 A8/B

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1936
Static Loaded Radius (mm)	895
Rolling Circumference (mm)	5871
SRI (mm)	925
Rim Rec	DW 16 A ; W 16 A ; DD 16
Rim Alt	W 16 L ; DD 16 L ; DW 16 L
ECE	E4-106R-000798
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2295	2635	2975	3315	3655	3955	4250	4650	5000
40	2295	2635	2975	3315	3655	3955	4250	4650	5000
30	2460	2825	3185	3550	3915	4235	4550	4975	5350
10 LT	3080	3535	3990	4445	4900	5300	5695	6230	6700
10 HT	2460	2825	3185	3550	3915	4235	4550	4975	5350

Printed on 4/27/2024 7:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..