

AGRIMAX RT 855 - Tekniska specifikationer



Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	520/85 R 38 (20.8 R 38)
LI/SS	155 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1849
Static Loaded Radius (mm)	813
Rolling Circumference (mm)	5466
SRI (mm)	875
Rim Rec	DW 16 L
Rim Alt	DW 18 L ; DD 16 L
ECE	E4-106R-000601
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	2170	2560	2910	3255	3565	3875
40	2170	2560	2910	3255	3565	3875
30	2325	2740	3115	3490	3820	4150
10 LT	2910	3430	3900	4365	4780	5195
10 HT	2325	2740	3115	3490	3820	4150

Printed on 4/27/2024 12:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..