

## AGRIMAX RT 855 - Tekniska specifikationer



### Description

AGRIMAX RT 855 erbjuder utmärkt dragförmåga och högklassig komfort. Det är huvudsakligen konstruerat för jordbearbetning och transporter på åker och väg, men vissa storlekar lämpar sig även för besprutning och vinskördning. AGRIMAX RT 855 har utmärkta självrensande egenskaper, så att föraren snabbt kan växla mellan åkerarbete och körning på väg.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Traktor • Skördemaskin för vingård

Version	SPECIAL
Type	TL
Tyre Size	520/85 R 38
LI/SS	170 A8/B

## Dimensions US Standard

Usa code	94061952
TMPH	1
Section Width (inch)	20.3
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	33.3
Rolling Circumference (inch)	220.3
Rim Rec	DW 16 L
Rim Alt	DW 18 L ; DD 16 L
ECE	E4-106R-001411
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	17	23	29	35	41	46	52
30	4780	5640	7180	8540	9790	10450	11510	12430	13230
25	4780	5640	7180	5840	9790	10450	11510	12430	13230
20	5130	6040	7690	9150	10480	11190	12320	13300	14150
5 LT	6420	7560	9620	11450	13120	14010	15420	16670	17720
5 HT	5130	6040	7690	9150	10480	11190	12320	13300	14150

Printed on 4/27/2024 11:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..