

AGRIMAX RT 945 - Tekniska specifikationer



Description

AGRIMAX RT 945 är ett specialkonstruerat däck för radgrödor: Det skadar inte grödan och bevarar skörden. Tack vare däckets utmärkta självrensande egenskaper kan föraren snabbt växla mellan åkerarbete och körning på väg, vilket är ännu ett bevis för AGRIMAX RT 945:s överlägsna prestanda. Den starka däckstommen ger däcket utmärkt stabilitet, enastående dragförmåga och imponerande hållbarhet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Traktor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 46 (12.4 R 46)
LI/SS	148 D/151 A8

Dimensions US Standard

Usa code	94051694
Section Width (inch)	12.6
Overall Diameter (inch)	68.7
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	206
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-004068
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52
40	2990	3890	4730	5210	5490	6050	6540	6940
30	3140	4090	4970	5480	5760	6350	6870	7300
25	3270	4270	5180	5710	6020	6620	7150	7610
20	3440	4480	5430	5990	6300	6940	7510	7980
5	4490	5840	7090	7810	8230	9070	9800	10420

Printed on 4/21/2024 12:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..