

AGRIMAX RT 955 - Tekniska specifikationer



Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	210/95 R 44 (8.3 R 44)
LI/SS	120 A8/B

Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1518
Static Loaded Radius (mm)	721
Rolling Circumference (mm)	4653
SRI (mm)	725
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-000771
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
50	660	760	870	980	1095	1205	1305	1400	-
40	660	760	870	980	1095	1205	1305	1400	-
30	705	810	930	1050	1170	1290	1395	1500	-
10	970	1115	1240	1365	1515	1660	1935	2040	2100

Printed on 4/27/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..