

AGRIMAX RT 955 - Tekniska specifikationer



Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	270/95 R 38 (11.2 R 38)
LI/SS	140 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1479
Static Loaded Radius (mm)	697
Rolling Circumference (mm)	4510
SRI (mm)	700
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000657
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	975	1275	1550	1700	1800	1975	2150	2325	2500	-
40	975	1275	1550	1700	1800	1975	2150	2325	2500	-
30	1045	1365	1660	1820	1930	2115	2305	2490	2675	-
10	1165	1465	1800	2140	2475	2550	2850	3150	3450	3750

Printed on 4/27/2024 10:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..