AGRIMAX RT 955 - Tekniska specifikationer

Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däckmönstret med rundad däckskuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och självrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

UM

US Standard

Construction

RADIAL

Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	270/95 R 46 (11.2 R 46)
LI/SS	143 A8/B

Dimensions US Standard

Usa code	94042555
Section Width (inch)	10.8
Overall Diameter (inch)	66.3
Static Loaded Radius (inch)	31.2
Rolling Circumference (inch)	203.5
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000785
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2470	3190	3850	4210	4510	4930	5360	5710	6000	-
25	2470	3190	3850	4210	4510	4930	5360	5710	6000	-
20	2650	3420	4120	4510	4830	5280	5730	6120	6440	-
5	3410	4410	5310	5820	6230	6810	7400	7890	8300	9020

Printed on 5/7/2024 6:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..