

## AGRIMAX RT 955 - Tekniska specifikationer



### Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	300/85 R 42 (11.2 R 42)
LI/SS	144 A8/B

## Dimensions US Standard

Usa code	94040636
Section Width (inch)	11.6
Overall Diameter (inch)	62.1
Static Loaded Radius (inch)	29.3
Rolling Circumference (inch)	190.9
Rim Rec	W 9
Rim Alt	W 10 ; W 11
ECE	E4-106R-001396
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
25	2540	3270	3960	4320	4630	5070	5500	5860	6150	-
20	2710	3510	4230	4630	4960	5420	5890	6280	6610	-
5	2880	3620	4450	5280	6120	6300	7040	7780	8520	9260

Printed on 4/21/2024 5:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..