

## AGRIMAX RT 955 - Tekniska specifikationer



### Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	300/95 R 52 (12.4 R 52)
LI/SS	151 A8/B

## Dimensions US Standard

Usa code	94029747
Section Width (inch)	11.6
Overall Diameter (inch)	74.4
Static Loaded Radius (inch)	35
Rolling Circumference (inch)	227.3
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E4-106R-001484
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
25	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
20	3190	4160	5060	5540	5870	6440	7010	7580	8150	-
5	3540	4450	5480	6500	7540	7760	8670	9590	10500	11410

Printed on 4/27/2024 10:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..