

AGRIMAX RT 955 - Tekniska specifikationer



Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 340/85 R 48 (13.6 R 48) |
| LI/SS | 152 A8/B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 353 |
| Overall Diameter (mm) | 1797 |
| Static Loaded Radius (mm) | 855 |
| Rolling Circumference (mm) | 5572 |
| SRI (mm) | 875 |
| Rim Rec | W 12 |
| Rim Alt | W 11 |
| ECE | E4-106R-000800 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | - |
| 40 | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | - |
| 30 | 1485 | 1940 | 2360 | 2585 | 2740 | 3005 | 3270 | 3535 | 3800 | - |
| 10 | 1655 | 2080 | 2560 | 3040 | 3515 | 3625 | 4050 | 4475 | 4900 | 5325 |

Printed on 4/21/2024 4:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..