

## AGRIMAX SIRIO - Tekniska specifikationer



### Description

AGRIMAX SIRIO är ett höghastighetsdäck (upp till 70 km/h) som har tagits fram av BKT för kraftfulla traktorer. Konstruktionen lämpar sig utmärkt för både transporter och jordbearbetning. Sidoväggen är särskilt flexibel för att säkerställa enastående stabilitet, hantering och komfort och ge en ännu bättre körupplevelse. Däcket är även tillgängligt med IF-teknologi, som möjliggör hög lastkapacitet vid lågt ringtryck. Det förstärkta däckhöljet och ett stort antal bälten är en garanti för överlägsen dragförmåga på åkern, samtidigt som det låga rullmotståndet bidrar till bättre bränsleekonomi.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Motorstark traktor

Version	HIGH SPEED
Type	TL
Tyre Size	540/65 R 30
LI/SS	150 D/147 E

## Dimensions US Standard

Usa code	94045310
Section Width (inch)	20.9
Overall Diameter (inch)	57.6
Static Loaded Radius (inch)	26.3
Rolling Circumference (inch)	173.2
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E4-106R-000814
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	3200	3670	4210	4750	5290	5830	6300	6780
40	3470	3990	4590	5170	5760	6360	6880	7390
30	3650	4200	4820	5430	6060	6680	7220	7760
25	3800	4380	5030	5670	6320	6970	7530	8090
15	4120	4730	5430	6130	6830	7530	8150	8750
5	5210	5990	6880	7760	8640	9530	10310	11080

Printed on 4/24/2024 10:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..