AGRIMAX SIRIO - Tekniska specifikationer

Description

AGRIMAX SIRIO är ett höghastighetsdäck (upp till 70 km/h) som har tagits fram av BKT för kraftfulla traktorer. Konstruktionen lämpar sig utmärkt för både transporter och jordbearbetning. Sidoväggen är särskilt flexibel för att säkerställa enastående stabilitet, hantering och komfort och ge en ännu bättre körupplevelse. Däcket är även tillgängligt med IF-teknologi, som möjliggör hög lastkapacitet vid lågt ringtryck. Det förstärkta däckhöljet och ett stort antal bälten är en garanti för överlägsen dragförmåga på åkern, samtidigt som det låga rullmotståndet bidrar till bättre bränsleekonomi.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Motorstark traktor

Version	HIGH SPEED
Type	TL
Tyre Size	IF 600/70 R 30
LI/SS	165 D/162 E

Dimensions International Standard

Section Width (mm)	603
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	713
Rolling Circumference (mm)	4759
SRI (mm)	750
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-000817
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4350	4685
From 65 to 40	2420	2780	3190	3605	4015	4425	4785	5150
30	2515	2890	3315	3745	4175	4600	4975	5355
25	2565	2945	3380	3820	4255	4690	5165	5560
20	2610	3000	3445	3890	4355	4775	5165	5560
10	3070	3530	4050	4575	5095	5615	6075	6540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 4:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..