

AGRIMAX SIRIO - Tekniska specifikationer



Description

AGRIMAX SIRIO är ett höghastighetsdäck (upp till 70 km/h) som har tagits fram av BKT för kraftfulla traktorer. Konstruktionen lämpar sig utmärkt för både transporter och jordbearbetning. Sidoväggen är särskilt flexibel för att säkerställa enastående stabilitet, hantering och komfort och ge en ännu bättre körupplevelse. Däcket är även tillgängligt med IF-teknologi, som möjliggör hög lastkapacitet vid lågt ringtryck. Det förstärkta däckhöljet och ett stort antal bälten är en garanti för överlägsen dragförmåga på åkern, samtidigt som det låga rullmotståndet bidrar till bättre bränsleekonomi.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Motorstark traktor

| | |
|-----------|----------------|
| Version | HIGH SPEED |
| Type | TL |
| Tyre Size | IF 600/70 R 30 |
| LI/SS | 165 D/162 E |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94044849 |
| Section Width (inch) | 23.7 |
| Overall Diameter (inch) | 63.1 |
| Static Loaded Radius (inch) | 28.1 |
| Rolling Circumference (inch) | 187.4 |
| Rim Rec | DW 21 B |
| Rim Alt | DW 20 B |
| ECE | E4-106R-000817 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---------------|------|------|------|-------|-------|-------|-------|-------|
| 45 | 4850 | 5570 | 6400 | 7240 | 8050 | 8880 | 9590 | 10330 |
| From 40 to 25 | 5340 | 6130 | 7040 | 7950 | 8860 | 9760 | 10550 | 11360 |
| 20 | 5550 | 6380 | 7310 | 8260 | 9210 | 10150 | 10970 | 11810 |
| 15 | 5660 | 6500 | 7460 | 8430 | 9390 | 10340 | 11180 | 12030 |
| 12 | 5760 | 6620 | 7600 | 8580 | 9560 | 10530 | 11390 | 12260 |
| 5 | 6770 | 7790 | 8930 | 10090 | 11240 | 12380 | 13400 | 14420 |

Printed on 4/24/2024 10:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..