AGRIMAX TURF RT 333 - Tekniska specifikationer

Description

AGRIMAX TURF RT 333 (R-3+) är ett radialdäck designat för små traktorer som används till trädgårdsskötsel, i fruktodlingar och på vingårdar. Den rundade däckskuldran ger låg jordpackning och gör däcket extremt skonsamt mot marken. Det unika, extra djupa däckmönstret (R-3+) och specialdesignen med riktat mönster ger utmärkt dragförmåga på både åkern och vägen, liksom ökad livslängd. AGRIMAX TURF RT 333 (R-3+) besitter enastående självrensande egenskaper och det låga rullmotståndet bidrar till betydande bränslebesparingar.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Skördemaskin för fruktodling • Liten traktor • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	320/70 R 20
LI/SS	113 A8/113 B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	982
Static Loaded Radius (mm)	441
Rolling Circumference (mm)	2916
SRI (mm)	450
Rim Rec	W10
Rim Alt	W9 ; W11
ECE	E11-106R-006944

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	635	740	840	945	1050	1150
40	635	740	840	945	1050	1150
30	680	795	905	1015	1125	1235
10 LT	850	990	1130	1270	1410	1545
10 HT	680	795	905	1015	1125	1235

Printed on 4/19/2024 2:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..