



# AGRIMAX V-FLECTO - Tekniska specifikationer



## Description

AGRIMAX V-FLECTO är BKT:s svar på de utmanande kraven beträffande både teknik och prestanda när det gäller motorstarka traktorer. Däcket passar perfekt till jordbearbetning och transportarbeten tack vare den minskade jordpackningen och självrensande egenskaper. Den innovativa VF-teknologin ger AGRIMAX V-FLECTO hög lastkapacitet med lägre ringtryck jämfört med standard- och IF-däck, och uppnår höga hastigheter. Det omfattar även NRO-teknologi, så att du kan sätta standardfälgar på däcket. BKT har konstruerat däcket med optimerad geometri för att förbättra förarkomforten både på åkern och vägen, och samtidigt minska bränsleförbrukningen.

## UM

US Standard

## Construction

RADIAL

## Machinery

Lantbruk: Motorstark traktor

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 28 NRO
LI/SS	163 D

## Dimensions US Standard

<b>Usa code</b>	94070930
<b>Section Width (inch)</b>	23.5
<b>Overall Diameter (inch)</b>	58.7
<b>Static Loaded Radius (inch)</b>	25.8
<b>Rolling Circumference (inch)</b>	175.3
<b>Rim Rec</b>	DW 21 B
<b>Rim Alt</b>	DW 20 B
<b>Narrow Rim option</b>	DW 18 L
<b>ECE</b>	E11-106R-007602
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
<b>45</b>	4990	5780	6560	7440	8130	8820	9790
<b>From 40 to 25</b>	5490	6350	7210	8170	8930	9680	10750
<b>20</b>	5600	6480	7350	8340	9100	9880	10970
<b>12</b>	5710	6600	7500	8500	9280	10060	11180
<b>5</b>	6040	6990	7930	8990	9820	10650	11830
<b>*Upto 5 Cyc with front loader</b>	7680	8880	10090	11440	12490	13550	15050
<b>5 HT</b>	5600	6480	7350	8340	9100	9880	10970

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 3:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..