

AGRIMAX V-FLECTO - Tekniska specifikationer



Description

AGRIMAX V-FLECTO är BKT:s svar på de utmanande kraven beträffande både teknik och prestanda när det gäller motorstarka traktorer. Däcket passar perfekt till jordbearbetning och transportarbeten tack vare den minskade jordpackningen och självrensande egenskaper. Den innovativa VF-teknologin ger AGRIMAX V-FLECTO hög lastkapacitet med lägre ringtryck jämfört med standard- och IF-däck, och uppnår höga hastigheter. Det omfattar även NRO-teknologi, så att du kan sätta standardfålgar på däcket. BKT har konstruerat däcket med optimerad geometri för att förbättra förarkomforten både på åkern och vägen, och samtidigt minska bränsleförbrukningen.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Motorstark traktor

Version	STANDARD
Type	TL
Tyre Size	VF 600/70 R 30 NRO
LI/SS	168 D

Dimensions US Standard

Usa code	94064601
Section Width (inch)	23.7
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	27.6
Rolling Circumference (inch)	185.5
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 B
ECE	E11-106R-006162

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	5610	6500	7410	8420	9310	10220	11230
From 40 to 25	6170	7150	8150	9260	10240	11230	12350
20	6290	7290	8300	9440	10440	11450	12590
12	6420	7430	8470	9620	10650	11670	12830
5	6790	7860	8950	10180	11250	12350	13580
*Upto 5 Cyc with front loader	8640	10010	11400	12960	14330	15720	17280
5 HT	6290	7290	8300	9440	10440	11450	12590

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 3:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..