

AGRIMAX V-FLECTO - Tekniska specifikationer



Description

AGRIMAX V-FLECTO är BKT:s svar på de utmanande kraven beträffande både teknik och prestanda när det gäller motorstarka traktorer. Däcket passar perfekt till jordbearbetning och transportarbeten tack vare den minskade jordpackningen och självrensande egenskaper. Den innovativa VF-teknologin ger AGRIMAX V-FLECTO hög lastkapacitet med lägre ringtryck jämfört med standard- och IF-däck, och uppnår höga hastigheter. Det omfattar även NRO-teknologi, så att du kan sätta standardfälgar på däcket. BKT har konstruerat däcket med optimerad geometri för att förbättra förarkomforten både på åkern och vägen, och samtidigt minska bränsleförbrukningen.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Motorstark traktor

Version	STANDARD
Type	TL
Tyre Size	VF 620/70 R 42
LI/SS	175D

Dimensions International Standard

Section Width (mm)	620
Overall Diameter (mm)	1935
Static Loaded Radius (mm)	849
Rolling Circumference (mm)	5795
SRI (mm)	925
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E11-106R-0011233

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3140	3640	4145	4710	5210	5715	6275
from 65 to 40	3450	4005	4555	5175	5730	6280	6900
30	3520	4085	4645	5280	5840	6405	7035
20	3590	4165	4740	5385	5960	6530	7175
10	3795	4405	5010	5695	6300	6910	7590
*Upto 10 Cyc with front loader	4830	5605	6380	7245	8020	8795	9660
10HT	3520	4085	4645	5280	5840	6405	7035

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 4:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..