



# AGRIMAX V-FLECTO - Tekniska specifikationer



## Description

AGRIMAX V-FLECTO är BKT:s svar på de utmanande kraven beträffande både teknik och prestanda när det gäller motorstarka traktorer. Däcket passar perfekt till jordbearbetning och transportarbeten tack vare den minskade jordpackningen och självrensande egenskaper. Den innovativa VF-teknologin ger AGRIMAX V-FLECTO hög lastkapacitet med lägre ringtryck jämfört med standard- och IF-däck, och uppnår höga hastigheter. Det omfattar även NRO-teknologi, så att du kan sätta standardfälgar på däcket. BKT har konstruerat däcket med optimerad geometri för att förbättra förarkomforten både på åkern och vägen, och samtidigt minska bränsleförbrukningen.

## UM

US Standard

## Construction

RADIAL

## Machinery

Lantbruk: Motorstark traktor

Version	STANDARD
Type	TL
Tyre Size	VF 750/70 R 44
LI/SS	186 D

## Dimensions US Standard

<b>Usa code</b>	94066926
<b>Section Width (inch)</b>	29.9
<b>Overall Diameter (inch)</b>	85.6
<b>Static Loaded Radius (inch)</b>	37.7
<b>Rolling Circumference (inch)</b>	253.9
<b>Rim Rec</b>	DW 25 B
<b>Rim Alt</b>	DW 24 B
<b>ECE</b>	E11-106R-006765
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
<b>45</b>	9530	11060	12590	14300	15830	17350	19060
<b>from 40 to 25</b>	10470	12150	13820	15710	17380	19060	20940
<b>20</b>	10680	12400	14110	16030	17740	19440	21360
<b>12</b>	10890	12640	14380	16340	18090	19830	21780
<b>5</b>	11520	13370	15210	17280	19120	20960	23040
<b>*Upto 5 Cyc with front loader</b>	14660	17010	19360	21990	24340	26690	29320
<b>5 HT</b>	10680	12400	14110	16030	17740	19440	21360

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/4/2025 4:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..