

AGRIMAX V-FLECTO - Ladda ned faktablad



Description

AGRIMAX V-FLECTO är BKT:s svar på de utmanande kraven beträffande både teknik och prestanda när det gäller motorstarka traktorer. Däcket passar perfekt till jordbearbetning och transportarbeten tack vare den minskade jordpackningen och självrensande egenskaper. Den exklusiva VF-teknologin ger AGRIMAX V-FLECTO hög lastkapacitet med lägre ringtryck jämfört med standard- och IF-däck, och uppnår höga hastigheter. Det omfattar även NRO-teknologi, så att du kan sätta standardfälgar på däcket. BKT har konstruerat däcket med optimerad geometri för att förbättra förarkomforten både på åkern och vägen, och samtidigt minska bränsleförbrukningen.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Motorstark traktor

| SIZE | Version | TRA Code | LI/SS | RIM REC | RIM ALT | NRO | SW | OD | SLR | RC | SRI | Type | ECE |
|--------------------|----------|----------|-------|---------|------------------------|---------|-----|------|-----|------|-----|------|-----------------|
| VF 480/60 R 28 NRO | STANDARD | R1W | 145 D | DW 16 L | W 16 L | W 15 L | 470 | 1290 | 571 | 3807 | 625 | TL | E11-106R-005496 |
| VF 520/60 R 28 NRO | STANDARD | R1W | 149 D | DW 18 L | W 18 L | DW 16 L | 516 | 1335 | 587 | 3910 | 650 | TL | E11-106R-005497 |
| VF 540/65 R 28 NRO | STANDARD | R1W | 154 D | DW 20 B | DW 18 L | DW 16 L | 549 | 1413 | 622 | 4160 | 675 | TL | E11-106R-005710 |
| VF 600/60 R 28 NRO | STANDARD | R1W | 157 D | DW 20 B | DW 18 L | DW 18 L | 587 | 1440 | 632 | 4228 | 675 | TL | E11-106R-004471 |
| VF 600/65 R 28 NRO | STANDARD | R1W | 163 D | DW 21 B | DW 20 B | DW 18 L | 597 | 1491 | 655 | 4453 | 700 | TL | E11-106R-007602 |
| VF600/70 R 28 | STANDARD | R1W | 167 D | DW 21 B | DW 20 B | | 603 | 1551 | 662 | 4572 | 725 | TL | E11-106R-008814 |
| VF 540/65 R 30 NRO | STANDARD | R1W | 158 D | DW 20 B | DW 18 L | DW 16 L | 549 | 1464 | 650 | 4351 | 700 | TL | E11-106R-005711 |
| VF 600/60 R 30 NRO | STANDARD | R1W | 158 D | DW 20 B | DW 18 L ; DW 21 B | DW 18 L | 595 | 1485 | 649 | 4404 | 700 | TL | E11-106R-002979 |
| VF 600/70 R 30 NRO | STANDARD | | 168 D | DW 21 B | DW 20 B | DW 18 B | 603 | 1602 | 702 | 4711 | 750 | TL | E11-106R-006162 |
| VF 600/65 R 34 NRO | STANDARD | R1W | 169 D | DW 21 B | DW 20 B | DW 18 L | 597 | 1644 | 731 | 4952 | 775 | TL | E11-106R-007603 |
| VF 650/60 R 34 | STANDARD | | 168 D | DW 23 B | DW21B | | 660 | 1676 | 750 | 4996 | 775 | TL | E11-106R-007210 |
| VF 710/60 R 34 NRO | STANDARD | R1W | 173 D | DW 25 B | DW 24 B ; DW 27 B | DW 23 B | 708 | 1716 | 752 | 5097 | 825 | TL | E11-106R-007201 |
| VF600/60 R 34 | STANDARD | R1W | 160 D | DW 20 B | DW 18 L ; DW 21 B | DW 18 L | 595 | 1584 | 691 | 4710 | 750 | TL | E11-106R-008773 |
| VF600/70 R 34 NRO | STANDARD | R1W | 170 D | DW 21 B | DW 20 B | DW 18 B | 603 | 1704 | 740 | 5040 | 800 | TL | E11-106R-008813 |
| VF650/65 R 34 NRO | STANDARD | R1W | 170 D | DW 23 B | DW 21 B | DW 20 B | 650 | 1710 | 761 | 5153 | 825 | TL | E11-106R-008812 |
| VF 480/80 R 38 | STANDARD | R1W | 166 D | DW 16 L | DW 15 L | | 479 | 1733 | 774 | 5169 | 825 | TL | E11-106R-007168 |
| VF 540/65 R 38 NRO | STANDARD | R1W | 162 D | DW 20 B | DW 18 L | DW 16 L | 549 | 1676 | 760 | 4981 | 800 | TL | E11-106R-005020 |
| VF 600/60 R 38 NRO | STANDARD | R1W | 168 D | DW 20 B | DW 18 L | DW 18 L | 587 | 1685 | 757 | 5077 | 800 | TL | E11-106R-006414 |
| VF 600/60 R 38 NRO | STANDARD | R1W | 166 D | DW 20 B | DW 18 L | DW 18 L | 587 | 1685 | 757 | 5081 | 800 | TL | E11-106R-005021 |
| VF 650/60 R 38 NRO | STANDARD | R1W | 173 D | DW 23 B | DW 21 B | DW 20 B | 650 | 1745 | 774 | 5217 | 825 | TL | E11-106R-006415 |
| VF 650/60 R 38 NRO | STANDARD | R1W | 166 D | DW 23 B | DW 21 B | DW 20 B | 650 | 1745 | 774 | 5231 | 825 | TL | E11-106R-005712 |
| VF 650/65 R 38 NRO | STANDARD | R1W | 169 D | DW 23 B | DW 21 B | DW 20 B | 650 | 1811 | 798 | 5387 | 875 | TL | E11-106R-005022 |
| VF 710/55 R 38 | STANDARD | R1W | 175 D | DW 25 B | DW 24 B | | 710 | 1750 | 780 | 5242 | 825 | TL | E11-106R-006844 |
| VF 710/60 R 38 NRO | STANDARD | R1W | 171 D | DW 25 B | DW 23 B | DW 23 B | 708 | 1820 | 794 | 5447 | 875 | TL | E11-106R-004520 |
| VF 710/70 R 38 | STANDARD | | 181 D | DW 24 B | DW 23 B ; DW 25 B | | 715 | 1961 | 843 | 5773 | 925 | TL | E11-106R-006163 |
| VF 710/75 R 38 | STANDARD | R1W | 183 D | DW 24 B | DW 23 B ; DW 25 B | | 720 | 2060 | 905 | 6151 | 950 | TL | E11-106R-006764 |
| VF 800/70 R 38 CFO | STANDARD | | 187 D | DW 28 B | DW25 B ; DW27B ; DW30B | | 804 | 2085 | 890 | 6155 | 975 | TL | E11-106R-007205 |
| VF900/60 R 38 NRO | STANDARD | R1W | 187 D | DW 30 B | | DW 27 B | 881 | 2045 | 882 | 6053 | 975 | TL | E11-106R-009004 |
| VF 520/85 R 42 CFO | STANDARD | R1W | 180 D | DW 18 L | | | 535 | 1951 | 876 | 5841 | 925 | TL | E11-106R-007169 |
| VF 580/85 R 42 | SPECIAL | R1W | 183 | DW20B | DW18B ; MW20B | | 606 | 2058 | 923 | 6166 | 975 | TL | E11-106R- |

| CFO | | | D | | | | | | | | | 006444 | | |
|---------------------------|----------|-----|-------|---------|-------------------|--|---------|------|------|------|------|--------|-----------------|-----------------|
| VF 580/85 R 42 CFO | STANDARD | R1W | 183 D | DW20B | DW18B ; MW20B | | 606 | 2058 | 923 | 6166 | 975 | TL | E11-106R-006444 | |
| VF 650/60 R 42 | STANDARD | | 174 D | DW 23 B | DW21B | | 660 | 1845 | 834 | 5564 | 875 | TL | E11-106R-008774 | |
| VF 650/65 R 42 NRO | STANDARD | R1W | 174 D | DW 23 B | DW 21 B | | DW 20 B | 650 | 1913 | 852 | 5773 | 925 | TL | E11-106R-005713 |
| VF 710/60 R 42 NRO | STANDARD | R1W | 173 D | DW 25 B | DW 23 B ; MW 25 B | | DW 23 B | 710 | 1930 | 860 | 5786 | 925 | TL | E11-106R-002998 |
| VF 710/70 R 42 | STANDARD | | 185 D | DW 25 B | DW 23 B ; DW 24 B | | | 715 | 2061 | 921 | 6182 | 975 | TL | E11-106R-006266 |
| VF 710/70 R 42 | STANDARD | | 193 D | DW 25 B | DW 23 B ; DW 24 B | | | 720 | 2058 | 921 | 6182 | 975 | TL | E11-106R-009053 |
| VF 900/60 R 42 NRO | STANDARD | | 189 D | DW 30B | | | DW 28 B | 900 | 2142 | 937 | 6390 | 1025 | TL | E11-106R-006165 |
| VF710/75 R 42 | STANDARD | R1W | 184 D | DW 24 B | DW 23 B ; DW 25 B | | | 730 | 2150 | 937 | 6412 | 1000 | TL | E11-106R-009074 |
| VF 750/70 R 44 | STANDARD | R1W | 186 D | DW 25 B | DW 24 B | | | 760 | 2175 | 958 | 6450 | 1025 | TL | E11-106R-006765 |
| VF 520/85 R 46 CFO | STANDARD | R1W | 173 D | DW 18 L | | | | 535 | 2052 | 911 | 6111 | 975 | TL | E11-106R-008662 |

Printed on 4/15/2024 2:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..