

AGRIMAXFACTOR - Tekniska specifikationer



Description

AGRIMAXFACTOR är BKT:s helt nya 70-serie för traktorer som passar perfekt både för transport- och jordbearbetningsbruk. Det förbättrade däckmönstret med ännu längre däckklackar och ändrad däckklackriktning står för bättre vägegenskaper. Den minskade däckklackvinkeln säkerställer lägre rullningsmotstånd medan kontaktytan mot marken som utökats med 5 % betydligt minskar det upplevda bullret i hytten – båda dessa funktioner står för ökad komfort. Dessutom ger det kraftfulla polyesterhöljet extraordinär lateral stabilitet och snabbare styrningsrespons även vid användning vid hög hastighet eller tung last. Däcket har utmärkta bromsresultat på våta ytor.

Kort sagt utgörs AGRIMAXFACTORs övergripande fördelar av god hantering i kombination med i flera avseenden extraordinär förarkomfort samt utmärkt hållbarhet – allt detta är särskilda krav för allt tyngre maskiner inklusive de tyngre vikterna hos elektriska fordons batteripaket. Den exklusiva sidoväggen visar den perfekt inriktade "E-READY"-logotypen som visar BKT:s engagemang för elektrisk rörlighet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	176 D/179 A8

Dimensions US Standard

Usa code	94070527
Section Width (inch)	28.2
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	36.8
Rolling Circumference (inch)	244
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-007525
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
40	6730	7830	8930	10020	11120	12210	13470	14250	15650
30	7080	8220	9370	10530	11670	12820	14140	14960	16430
25	7350	8540	9740	10930	12140	13330	14690	15550	17080
20	7750	9010	10260	11530	12790	14040	15490	16390	18000
5 LT	9030	10490	11960	13430	14900	16370	18040	19090	20980
5 HT	7750	9010	10260	11530	12790	14040	15490	16390	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/5/2024 4:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..