

AIROMAX AM 27 - Ladda ned faktablad



Description

AIROMAX AM 27 är det idealiska vägorienterade däck för användning på kranar för bygg- och anläggningsändamål. Det är extra värmetåligt och har enastående åkkomfort. AIROMAX AM 27 är ett höghastighetsdäck som är särskilt lämpat för arbeten som kräver hög manövrerbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Kranbil

| SIZE | Version | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | ECE |
|---|----------|-------|-----------|-----------------------------|-----|------|-----|------|------|-----------------|
| 385/95 R 24 (14.00 R 24) | STANDARD | 170 F | 10.00W | | 372 | 1363 | 626 | 4175 | TT | E11-54R-0015910 |
| 385/95 R 25 (14.00 R 25) | STANDARD | 170 F | 10.00/1.5 | | 372 | 1363 | 626 | 4175 | TL | E11-54R-0015911 |
| 445/95 R 25 (16.00 R 25) | STANDARD | 174 F | 11.25/2.0 | 11.00/1.7 CR ; 11.00/1.7CRL | 440 | 1490 | 695 | 4587 | TL | E4-54R-0028867 |
| 505/95 R 25 (18.00 R 25) | STANDARD | 186 E | 13.00/2.5 | | 492 | 1600 | 728 | 4900 | TL | |
| 525/80 R 25 (20.5 R 25) | STANDARD | 176 F | 17.00/2.0 | 17.00/1.7 CR | 530 | 1481 | 681 | 4534 | TL | E11-54R-0016681 |

Printed on 4/27/2024 9:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..