

AIROMAX AM 543 - Tekniska specifikationer



Description

AIROMAX AM 543 är det idealiska däck för användning på kranar för bygg- och anläggningsändamål. Det har utomordentlig dragkraft och hög stabilitet. AIROMAX AM 543 är designat för att vara mycket värmetåligt eftersom krandäck utsätts för stora belastningar och extrema användningsförhållanden. Det passar dessutom för alla arbeten som kräver hög manövrerbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Kranbil

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 E

Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00/1.5

Load capacity (Kg)

km/h / bar	9.00
70	6000

Printed on 4/17/2024 5:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..