

AIROMAX AM 28 WINTER - Tekniska specifikationer



Description

AIROMAX AM28 WINTER har utformats speciellt för höghastighetsmobilkranar inom byggbranschen. Faktum är att detta BKT-däck har optimerats för att möta utmanande uppgifter på byggarbetsplatser som kräver exakt hantering i höga hastigheter upp till 80 km/h (50mph). AIROMAX AM28 WINTER är tillverkad av en särskilt värmebeständig blandning – en viktig egenskap i sådana krävande miljöer. Det specialutvecklade slitbanemönstret med flera små, tandade spår ger exceptionellt bra grepp och dragkraft, vilket motverkar sladd även på is och snö. Dessutom ger däckets enastående och smidig körkomfort, även under tung drift.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Kranbil

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	174 F

Dimensions International Standard

Overall Width (mm)	435
Overall Diameter (mm)	1487
Static Loaded Radius (mm)	694
Rolling Circumference (mm)	4578
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL
ECE	E4-54R-0022146

Load capacity (Kg)

km/h / bar	9.00
30	8500
40	7750
50	7500
60	7300
70	7100
80	6700
90	6300
100	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 8:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..