ARROW - Tekniska specifikationer

Description

ARROW lämpar sig för transportarbeten med släpvagn. Det har ett väginriktat däck med lång hållbarhet och längre livslängd. ARROW har hög lastkapacitet även vid höga hastigheter. En "HD"-version med en speciell gummiblandning är också tillgänglig för användare som kräver bättre prestanda.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Släpvagn

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions US Standard

Usa code	94022496
Ply Rating	16
Section Width (inch)	10.6
Overall Diameter (inch)	40.9
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

Load capacity (lbs)

mph / psi	**-**	**-**
-	-	-
-	-	-

Printed on 4/24/2024 2:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..