AS 504 - Tekniska specifikationer

Description

AS 504 är ett industridäck för lantbruk som huvudsakligen är konstruerat för jordbearbetning och materialhantering. Däcket besitter utmärkta självrensande egenskaper och ger bättre grepp, vilket gör att det lämpar sig för åkersläp och teleskoplastare. AS 504 finns i flera versioner för att uppfylla specifika kundbehov: ”HD”-versionen är tillverkad i en speciell gummiblandning med hög motståndskraft mot skärande underlag och punktering, medan ”special”-versionen har ett förstärkt däckhölje som ger längre livslängd.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Teleskoplastare • Åkersläp
Industri: Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	290
Overall Diameter (mm)	867
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2540
SRI (mm)	410
Rim Rec	9.00
ECE	E4-106R-001892

Load capacity (Kg)

km/h / bar	2.70
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Printed on 4/20/2024 10:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..