

AS 504 - Tekniska specifikationer



Description

AS 504 är ett industridäck för lantbruk som huvudsakligen är konstruerat för jordbearbetning och materialhantering. Däcket besitter utmärkta självrensande egenskaper och ger bättre grepp, vilket gör att det lämpar sig för åkersläp och teleskoplastare. AS 504 finns i flera versioner för att uppfylla specifika kundbehov: "HD"-versionen är tillverkad i en speciell gummblandning med hög motståndskraft mot skärande underlag och punktering, medan "special"-versionen har ett förstärkt däckhölje som ger längre livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Teleskoplastare • Åkersläp
Industri: Teleskoplastare

| | |
|--------------------|--------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 12.5/80 - 18 |
| LI/SS DRIVE WHEEL | 129 A8 |
| LI/SS FREE ROLLING | 142 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 308 |
| Overall Diameter (mm) | 987 |
| Static Loaded Radius (mm) | 438 |
| Rolling Circumference (mm) | 2892 |
| SRI (mm) | 475 |
| Rim Rec | W 9 |
| Rim Alt | 9 ; 11 |
| ECE | E11-106R-004346 |

Load capacity (Kg)

| | km/h / bar | 3.70 |
|--|------------|------|
| | 10 FR | 3710 |
| | 25 FR | 3155 |
| | 30 FR | 2970 |
| | 40 FR | 2650 |
| | 10 DW | 2590 |
| | 25 DW | 2200 |
| | 30 DW | 2070 |
| | 40 DW | 1850 |

Printed on 4/28/2024 1:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..