

AS 504 - Tekniska specifikationer



Description

AS 504 är ett industridäck för lantbruk som huvudsakligen är konstruerat för jordbearbetning och materialhantering. Däcket besitter utmärkta självrensande egenskaper och ger bättre grepp, vilket gör att det lämpar sig för åkersläp och teleskoplastare. AS 504 finns i flera versioner för att uppfylla specifika kundbehov: "HD"-versionen är tillverkad i en speciell gummblandning med hög motståndskraft mot skärande underlag och punktering, medan "special"-versionen har ett förstärkt däckhölje som ger längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Teleskoplastare • Åkersläp
Industri: Teleskoplastare

Version	INDUSTRIAL
Type	TL
Tyre Size	400/80 - 24
LI/SS	162 A8

Dimensions US Standard

Usa code	94035267
Section Width (inch)	15.5
Overall Diameter (inch)	49.7
Static Loaded Radius (inch)	22.3
Rolling Circumference (inch)	143.9
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-003633

Load capacity (lbs)

mph / psi	73
5	13090
15	11100
20	10890
25	10470

Printed on 4/28/2024 3:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..