AS 504 - Tekniska specifikationer

Description

AS 504 är ett industridäck för lantbruk som huvudsakligen är konstruerat för jordbearbetning och materialhantering. Däcket besitter utmärkta självrensande egenskaper och ger bättre grepp, vilket gör att det lämpar sig för åkersläp och teleskoplastare. AS 504 finns i flera versioner för att uppfylla specifika kundbehov: ”HD”-versionen är tillverkad i en speciell gummiblandning med hög motståndskraft mot skärande underlag och punktering, medan ”special”-versionen har ett förstärkt däckhölje som ger längre livslängd.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Teleskoplastare • Åkersläp
Industri: Teleskoplastare

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS DRIVE WHEEL	83 A8
LI/SS FREE ROLLING	95 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	164
Overall Diameter (mm)	735
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2190
SRI (mm)	350
Rim Rec	4.00 E
Rim Alt	4.50 E ; 4½ K
ECE	E4-106R-002836

Load capacity (Kg)

km/h / bar	2.80
10 FR	965
25 FR	820
30 FR	775
40 FR	690
10 DW	680
25 DW	575
30 DW	545
40 DW	485

Printed on 4/25/2024 2:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..