AS 504 - Tekniska specifikationer

Description

AS 504 är ett industridäck för lantbruk som huvudsakligen är konstruerat för jordbearbetning och materialhantering. Däcket besitter utmärkta självrensande egenskaper och ger bättre grepp, vilket gör att det lämpar sig för åkersläp och teleskoplastare. AS 504 finns i flera versioner för att uppfylla specifika kundbehov: ”HD”-versionen är tillverkad i en speciell gummiblandning med hög motståndskraft mot skärande underlag och punktering, medan ”special”-versionen har ett förstärkt däckhölje som ger längre livslängd.

UM

US Standard

Construction

BIAS

Machinery

Lantbruk: Teleskoplastare • Åkersläp
Industri: Teleskoplastare

Version	ARAMID BELTED
Type	TL
Tyre Size	7.00 - 12
LI/SS DRIVE WHEEL	88 A8
LI/SS FREE ROLLING	100 A8

Dimensions US Standard

Usa code	94044139
Ply Rating	8
Section Width (inch)	7.4
Overall Diameter (inch)	26.9
Static Loaded Radius (inch)	12.2
Rolling Circumference (inch)	80.7
Rim Rec	4.5
ECE	E11-106R-003382

Load capacity (lbs)

mph / psi	48
5 FR	2470
15 FR	2090
20 FR	1970
25 FR	1760
5 DW	1730
15 DW	1470
20 DW	1380
25 DW	1230

Printed on 4/20/2024 12:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..