

AS 507 - Tekniska specifikationer



Description

AS 507 är lämpligt för jordbearbetning med släp och arbetsfordon. Det besitter utmärkta självrensande egenskaper och har ökad dragförmåga på marken.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	185/65 - 15
LI/SS DRIVE WHEEL	76 A8
LI/SS FREE ROLLING	89 A8

Dimensions US Standard

Usa code	94019489
Ply Rating	4
Section Width (inch)	7.3
Overall Diameter (inch)	25.2
Static Loaded Radius (inch)	11.9
Rolling Circumference (inch)	74.6
Rim Rec	5½ J
ECE	E4-106R-002185

Load capacity (lbs)

mph / psi	41
5 FR	1790
15 FR	1520
20 FR	1430
25 FR	1280
5 DW	1230
15 DW	1050
20 DW	990
25 DW	880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 6:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..