

AT 110 - Tekniska specifikationer



Description

AT 110 är BKT:s däck som passar till terrängkörning med fyrhjulingar. Tack vare den imponerande styrkontrollen är AT 110 det idealiska framaxeldäcket till ditt fordon.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 8 - 10

Dimensions US Standard

Usa code	94000807
Ply Rating	4
Section Width (inch)	8
Overall Diameter (inch)	21.6
Rim Rec	6.5 AT
Rim Alt	6.0 AT

Load capacity (lbs)

mph / psi	5
50	240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 08:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..