AT 111 HD - Tekniska specifikationer

Description

AT 111 HD passar till terrängsport med fyrhjulingar. Det utökade mönsterdjupet och tjock sidovägg ger extra bra grepp och bromskontroll – för att inte tala om enastående dragförmåga och höghastighetskontroll i branta backar. AT 111 HD har längre livslängd.

UM

International Standard

Construction

BIAS

Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	TL
Tyre Size	AT 20 X 11 - 10

Dimensions International Standard

Ply Rating	6
Section Width (mm)	279
Overall Diameter (mm)	505
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E4-75R-0006327

Load capacity (Kg)

km/h / bar	0.45
100	150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 11:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..