

## AT 111 HD - Tekniska specifikationer



### Description

AT 111 HD passar till terrängsport med fyrhjulingar. Det utökade mönsterdjupet och tjock sidovägg ger extra bra grepp och bromskontroll – för att inte tala om enastående dragförmåga och höghastighetskontroll i branta backar. AT 111 HD har längre livslängd.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Fyrhjulning

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 11 - 10

## Dimensions International Standard

<b>Ply Rating</b>	6
<b>Section Width (mm)</b>	279
<b>Overall Diameter (mm)</b>	560
<b>Rim Rec</b>	9.0 AT
<b>Rim Alt</b>	8.5 AT
<b>ECE</b>	E4-75R-0006333

## Load capacity (Kg)

	km/h / bar	0.45
	100	175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 2:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..