

AT 111 HD - Tekniska specifikationer



Description

AT 111 HD passar till terrängsport med fyrhjulingar. Det utökade mönsterdjupet och tjock sidovägg ger extra bra grepp och bromskontroll – för att inte tala om enastående dragförmåga och höghastighetskontroll i branta backar. AT 111 HD har längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Fyrhjulig

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | AT 22 X 11 - 9 |

Dimensions US Standard

| | |
|-------------------------|----------------|
| Usa code | 94026890 |
| Ply Rating | 6 |
| Section Width (inch) | 11 |
| Overall Diameter (inch) | 22 |
| Rim Rec | 9.0 AT |
| Rim Alt | 8.5 AT |
| ECE | E4-75R-0006332 |

Load capacity (lbs)

| | |
|-----------|-----|
| mph / psi | 7 |
| 62 | 395 |

Printed on 4/24/2024 7:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..