

AT 316 - Tekniska specifikationer



Description

AT 316 passar kompaktraktorer av den typ som används vid kommunala arbeten och underhållsarbeten. Den speciella mönsterdesignen ger utmärkt dragkraft utan att kompromissa med fältskyddet - en viktig funktion för den här typen av arbeten. AT 316 finns även tillgängligt i en aramidbältad version med extra skydd mot punkteringar.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Kompaktraktor

Version	STANDARD
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions US Standard

Usa code	94001200
Ply Rating	4
Section Width (inch)	12.4
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.7
Rolling Circumference (inch)	69.6
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004082

Load capacity (lbs)

mph / psi	20
10	1710

Printed on 4/23/2024 12:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..