

AT 603 - Tekniska specifikationer



Description

AT 603 är ett diagonaldäck för grävarbeten och lastning inom jordbruksindustrin. Det passar bra för traktorgrävare, kompaktlastare och kompakta dumprar. AT 603 har konstruerats för att ge mycket bra dragkraft på drivhjulen och ge bästa möjliga prestanda på både vägar och i terräng. Specialversionen av AT 603 har ett förbättrat skydd mot skär- och skrapskador medan HD-versionen är idealisk för tung användning.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Grävlastare • Arbetsfordon

Industri: Grävlastare

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	274
Overall Diameter (mm)	907
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2727
SRI (mm)	425
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E4-106R-002325

Load capacity (Kg)

km/h / bar	3.70
10 FR	2730
25 FR	2320
30 FR	2185
40 FR	1950
10 DW	1905
25 DW	1620
30 DW	1525
40 DW	1360

Printed on 4/20/2024 6:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..