

## AT 603 - Tekniska specifikationer



### Description

AT 603 är ett diagonaldäck för grävarbeten och lastning inom jordbruksindustrin. Det passar bra för traktorgrävare, kompaktlastare och kompakta dumprar. AT 603 har konstruerats för att ge mycket bra dragkraft på drivhjulen och ge bästa möjliga prestanda på både vägar och i terräng. Specialversionen av AT 603 har ett förbättrat skydd mot skär- och skrapskador medan HD-versionen är idealisk för tung användning.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Grävlastare • Arbetsfordon  
Industri: Grävlastare

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions US Standard

Usa code	94019526
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	107.4
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E4-106R-002325

## Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 4/18/2024 3:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..