

AT 603 - Tekniska specifikationer



Description

AT 603 är ett diagonaldäck för grävarbeten och lastning inom jordbruksindustrin. Det passar bra för traktorgrävare, kompaktlastare och kompakta dumprar. AT 603 har konstruerats för att ge mycket bra dragkraft på drivhjulen och ge bästa möjliga prestanda på både vägar och i terräng. Specialversionen av AT 603 har ett förbättrat skydd mot skär- och skrapskador medan HD-versionen är idealisk för tung användning.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Grävlastare • Arbetsfordon
Industri: Grävlastare

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	308
Overall Diameter (mm)	1000
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	3027
SRI (mm)	475
Rim Rec	W 9
Rim Alt	11
ECE	E4-106R-004350

Load capacity (Kg)

	km/h / bar	3.70
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650
	10 DW	2590
	25 DW	2200
	30 DW	2070
	40 DW	1850

Printed on 4/18/2024 4:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..