

AT 603 - Tekniska specifikationer



Description

AT 603 är ett diagonaldäck för grävarbeten och lastning inom jordbruksindustrin. Det passar bra för traktorgrävare, kompaktlastare och kompakta dumprar. AT 603 har konstruerats för att ge mycket bra dragkraft på drivhjulen och ge bästa möjliga prestanda på både vägar och i terräng. Specialversionen av AT 603 har ett förbättrat skydd mot skär- och skrapskador medan HD-versionen är idealisk för tung användning.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Grävlastare • Arbetsfordon
Industri: Grävlastare

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

Dimensions US Standard

Usa code	94019663
Ply Rating	16
Section Width (inch)	12.1
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	119.2
Rim Rec	W 9
Rim Alt	11
ECE	E11-106R-004351

Load capacity (lbs)

mph / psi	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Printed on 4/18/2024 7:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..