

## AT 621 - Tekniska specifikationer



### Description

AT 621 är lämpligt för grävlastare och kompakthjullastare vid alla former av gräv- och lastarbeten i lantbruket. AT 621-däcket har extra djupt mönster, vilket ger hög motståndskraft mot skärande underlag och punkteringar samt längre livslängd. Dessutom besitter det här BKT-däcket mycket goda självrensande egenskaper och erbjuder ökad hållbarhet. AT 621 finns i flera versioner för att uppfylla högst skiftande kundbehov.

### UM

US Standard

### Construction

 BIAS

### Machinery

Lantbruk: Kompakthjullastare • Grävlastare  
Industri: Grävlastare • Hjullastare

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 28
LI/SS	154 A8

## Dimensions US Standard

Usa code	94069675
Ply Rating	14
Section Width (inch)	17.7
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	165.3
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-007209
TRA Code	R4

## Load capacity (lbs)

mph / psi	42
25	8250

Printed on 4/26/2024 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..