

AT 621 - Tekniska specifikationer



Description

AT 621 är lämpligt för grävlastare och kompakthjullastare vid alla former av gräv- och lastarbeten i lantbruket. AT 621-däcket har extra djupt mönster, vilket ger hög motståndskraft mot skärande underlag och punkteringar samt längre livslängd. Dessutom besitter det här BKT-däcket mycket goda självrensande egenskaper och erbjuder ökad hållbarhet. AT 621 finns i flera versioner för att uppfylla högst skiftande kundbehov.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Kompakthjullastare • Grävlastare
Industri: Grävlastare • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	400/70 - 20
LI/SS	152 B/168 A2

Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	494
Rolling Circumference (mm)	3271
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
TRA Code	R4

Load capacity (Kg)

km/h / bar	4.00	5.00
50	3550	-
10	-	5600

Printed on 4/26/2024 9:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..