

## AT 625 - Tekniska specifikationer



### Description

AT 625 är ett däck för grävarbeten och lastning inom jordbruksverksamheter. Det passar bra för traktorgrävare och kompaktlastare. Det extra djupa mönstret ger ett utomordentligt skydd mot punkteringar samt högre pålitlighet. AT 625 har utmärkt dragkraft och stabilitet, och ett förbättrat skydd mot skär- och skrapskador.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Grävlastare • Kompakthjullastare

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	645
Rolling Circumference (mm)	4254
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.60
40	3550

Printed on 4/24/2024 9:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..