

## AW 09 - Tekniska specifikationer



### Description

AW 09 har utvecklats för jordbearbetning, höskördning och transportarbeten med arbetsfordon, balpressar och släp. Det är idealiskt för det moderna lantbruket och kan köras både på väg och i terräng. Den förstärkta däckstommen ger hög lastkapacitet och längre livslängd för däcket. AW 09 har konstruerats med en speciell gummiblandning med motståndskraft mot skärande underlag och punkteringar vilket ger extraordinär motståndskraft mot stubb.

### UM

US Standard

### Construction

🌿 BIAS

### Machinery

Lantbruk: Balpress • Höskördemaskin • Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions US Standard

Usa code	94037919
Section Width (inch)	10.6
Overall Diameter (inch)	29.6
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	86.9
Rim Rec	9.00
ECE	E4-106R-000374

## Load capacity (lbs)

mph / psi	73
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 4/27/2024 11:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..