

## AW-18 - Tekniska specifikationer



### Description

AW-18 är framtagna för släpvagnar och maskiner som används för jordbearbetning. Dess särskilda utformning med icke-riktade ribbor och rundat axelområde undviker skördeskador under manövrering. Trådmönstret är särskilt utvecklat för att säkerställa förstklassiga självrengörande egenskaper. AW-18 står också för bästa körkomfort och minskad bränsleförbrukning.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3 (300/80 - 15.3)
LI/SS FREE ROLLING	139 A8

## Dimensions International Standard

Section Width (mm)	297
Overall Diameter (mm)	845
Rim Rec	9.00
ECE	E11-106R-006020

## Load capacity (Kg)

km/h / bar	4.75
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430

Printed on 4/18/2024 8:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..