

AW-18 - Ladda ned faktablad



Description

AW-18 är framtagna för släpvagnar och maskiner som används för jordbearbetning. Dess särskilda utformning med icke-riktade ribbor och rundat axelområde undviker skördeskador under manövrering. Trådmönstret är särskilt utvecklat för att säkerställa förstklassiga självrengörande egenskaper. AW-18 står också för bästa körkomfort och minskad bränsleförbrukning.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon

SIZE	Version	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	Type	ECE
11.5/80 - 15.3 (300/80 - 15.3)	STANDARD	139 A8	9.00		297	845	TL	E11-106R-006020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/14/2025 5:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..