

AW 702 - Tekniska specifikationer



Description

AW 702 har utvecklats för arbetsfordon, släpvagnar och balpressar inom jordbearbetning och transportarbeten. Det robusta däcket har konstruerats av BKT för att erbjuda hållbarhet i en klass för sig. AW 702 finns i flera versioner för att uppfylla specifika kundbehov: Det finns en variant med "stålförstärkt bälte" för kunder som behöver extra motståndskraft mot punktering, medan "HD"-versionen är tillverkad i en speciell gummiblandning med motståndskraft mot skärande underlag och punktering. "Special"-versionen erbjuder enastående motståndskraft mot stubb.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn
Industri: Släpvagn

| | |
|--------------------|----------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 10.0/75 - 15.3 |
| LI/SS FREE ROLLING | 119 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94008995 |
| Ply Rating | 8 |
| Section Width (inch) | 10.8 |
| Overall Diameter (inch) | 29.9 |
| Static Loaded Radius (inch) | 13.8 |
| Rolling Circumference (inch) | 87.1 |
| Rim Rec | 9.00 |

Load capacity (lbs)

| mph / psi | 45 |
|-----------|------|
| 5 FR | 4200 |
| 15 FR | 3570 |
| 20 FR | 3360 |
| 25 FR | 3000 |

Printed on 4/28/2024 1:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..