

AW 702 - Tekniska specifikationer



Description

AW 702 har utvecklats för arbetsfordon, släpvagnar och balpressar inom jordbearbetning och transportarbeten. Det robusta däcket har konstruerats av BKT för att erbjuda hållbarhet i en klass för sig. AW 702 finns i flera versioner för att uppfylla specifika kundbehov: Det finns en variant med "stålförstärkt bälte" för kunder som behöver extra motståndskraft mot punktering, medan "HD"-versionen är tillverkad i en speciell gummiblandning med motståndskraft mot skärande underlag och punktering. "Special"-versionen erbjuder enastående motståndskraft mot stubb.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn
Industri: Släpvagn

Version	STANDARD
Type	TT
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94009459
Ply Rating	14
Section Width (inch)	11.7
Overall Diameter (inch)	33.2
Static Loaded Radius (inch)	14.6
Rolling Circumference (inch)	97.4
Rim Rec	9.00
ECE	E4-106R-001897

Load capacity (lbs)

mph / psi	69
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/28/2025 12:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..