

AW 705 - Tekniska specifikationer



Description

AW 705 har utvecklats för arbetsfordon, släpvagnar och balpressar inom jordbearbetning och transportarbeten. Det är idealiskt för det moderna lantbruket tack vare förbättrad hållbarhet och hög lastkapacitet.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Balpress • Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	138 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	381
Overall Diameter (mm)	850
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2575
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E4-106R-001549

Load capacity (Kg)

km/h / bar	3.10
10 FR	3305
25 FR	2810
30 FR	2645
40 FR	2360

Printed on 4/25/2024 8:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..